





Mobile heated cabinets for **Heavy-Duty Transporting.** Universal angles for

12" X 20" Pans and/or 18" X 26" Trays.

MODELS





MOBILE HEATED CABINET



Special Height (60") permits you to see over the top



8" Semi-Pneumatic Casters to move over any surface. All casters have brakes



All Swivel Casters to get into the tightest corner



Universal Angles will hold sheet pans and steam pans securely in transport



Capacity of 250 lbs per bracket



Capacity of Cabinet is 22 (12" X 20" x 2 1/2") pans or multiples of 4" and 6" and/or 11 (18" x 26") trays



Magnetic/Mechanical Latch for positive closing



Door has 8 1/2" X 11" Card Holder



Three Heavy-Duty Hinges to ensure the door will always close correctly



Angle Steel Framed Door has adjustable damper



11 Gauge Stainless Steel Transport Latch for long distance moving/security



Heavy-duty, Chrome-Plated, Steel Push Handles



Heavy-Duty Bumper System, with additional support for loading assistance



Efficient **Armor Heat® System** draws only 8.6 amps for use anywhere



Temperature ranges from 60 to 230 degrees




All-Welded Angle Steel Frame


MODEL SPECIFICATIONS
















MODEL#	CAPACITY 18 " X 26" trays - 2 1/2" pans	WIDTH DIM A	DEPTH DIM B	HEIGHT DIM C	WATTAGE	AMPERAGE	SHIP WEIGHT
M11UA RW Road Warrior	11 sets U/A	28 1/2"	38"	60 1/16"	990	8.25	530 Lbs.



GENERAL

Cabinet constructed throughout with stainless steel. All double-wall construction insulated with high-density fiberglass insulation. All exterior surfaces shall be ground and polished to a #4 finish. Cabinet comes complete with heavy-duty push handles, cord wrap, bumper with "T" bar, transport latch on door, card holder on door, and 8" casters.



INNER CABINET

Inner cabinet shall be all 24 gauge 300 series stainless steel. Universal angles constructed of heavy gauge wire and vertical and horizontal 11 gauge flat stock. Each pair shall accommodate 250 lbs. Chrome-plated with heavy nickel and a clear coat. Angles adjustable on 1 1/2" centers. Holding posts removable for cleaning. Angles will accommodate 2 (12" X 20") pans or 1 (18" X 26") tray or 2 (14" X 18") trays.



DOOR

Door shall be all 20 gauge stainless steel. Door shall have full interior frame constructed of 3/4" X 3/4" 14 gauge Galvanized angle steel. Door shall be fully insulated and gasketed. Dóor shall have an exterior louver with an interior damper for moisture control. All door hardware shall be secured through framing in cabinet and door. Door shall have a 8 1/2" X 11" menu card holder. Door shall have a heavy-duty positive and magnetic door latch and heavy-duty refrigeration-type door hinges. Doors shall have 11 gauge stainless steel transport latch that will accept a padlock.



ELECTRICAL CHARACTERISTICS

Each cabinet shall have a top-mounted control panel consisting of an on/off switch with power indicator light, electronic temperature control with digital display. Each cabinet shall be heated by a 120 volt, 60 cycle, 1 phase, Armor Heat® system. Cabinet shall come complete with a permanently mounted 8' cord with a Nema #5-15P plug and cord wrap. Top of cabinet is removable for easy access to controls.



CASTERS

Cabinet shall have 4 heavy-duty, 8" casters, 4 swivel casters with brakes mounted to 6" X 6" X 5/16" steel plate drilled and tapped. Cabinet shall have a full wrap around rubber bumper. Bumper frame shall be 1/8" formed steel plate with aluminum cover, with bumper channels welded and riveted to bumper frame. Bumper frame is secured to bottom of the cabinet with 1/4" screws.



BASE FRAME

1/8" formed steel base. Base shall have four 6" X 6" X 5/16", steel plates drilled and tapped to accommodate 5", 6", or 8" casters. The plates are fully welded to frame on all 4 sides.



INTERNAL FRAME

All vertical and horizontal edges framed with a combination of 1 1/2" X 1 1/2" X 1/8" and 1" X 1 1/8" angle steel, arc welded, cross braced and reinforced at all corners.



ACCESSORIES, OPTIONS, VARIATIONS



Left-Hand Hinged Doors



Tamper-Proof Fasteners



Choice of Heavy-Duty Casters, 5" X 2", 6" and 8"



Control Panel Cover, Lockable



Cord Reel



Sterno Adapter



Stainless Steel Welded Door Hinge

STANDARD



Heavy-Duty Push Handle



Heavy-Duty Transport Latch



Heavy-Duty 8" Casters



Cord Wrap