

SECO

SELECT

TEST OUR METAL®



INSULATED MOBILE HEATED CABINET

For **18" X 26"**, **14" X 18"** Trays
and **12" X 20"** Hotel Pans

MODEL

**VCHI-30
RFM**

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacement for previously purchased equipment.

Job: _____

Item No. _____

INSULATED MOBILE HEATED CABINET



Double-Wall Construction with reinforcement channels welded between corner posts for added support and rigidity.



Fully Insulated Top, Sides and Door for energy efficiency and heat retention.



Aluminum Interior for even heat retention and energy efficiency.



Designed to hold **18" X 26", 14" X 18" Trays** and **12" X 20" Hotel Pans** with variable spacing on 3 1/8" centers. The tray slides are easily removable for cleaning.



SECOSelect® 1500 Watt Stainless Steel Heating Unit is removable from the front.



Doors Open 270 Degrees and are equipped with center reinforcement and heavy-duty flag hinges. Comes standard with built-in, flush mounted door handle.



20 Gauge Aluminum Exterior for durability and cleanability.



Heavy-Duty Frame and **Interlocking Side Panels** of 6063-T5 architectural aluminum for air tight seal and structural rigidity.

ACCESSORIES, OPTIONS, VARIATIONS



Top Perimeter Bumper



Transport Locks



Door Gaskets



Left-Hand Door
(no additional charge)






PTS - Pass Through



Perimeter Bumper Guard

MODEL SPECIFICATIONS



MODEL #	TRAY CAPACITY		PAN CAPACITY	HEIGHT DIM A	WIDTH DIM B	DEPTH DIM C	VOLTAGE	SHIPPING CUBE FEET	SHIP WEIGHT
	18" X 26"	14" X 18"							
VCHI-30-RFM	7	14	14	30 3/8"	27 5/8"	30 3/4"	120	25	150 Lbs.



GENERAL

Cabinet shall be constructed with an aluminum exterior and interior. All double-wall construction insulated with high-density fiberglass insulation. All exterior surfaces shall be ground and polished to a #3 finish.



INNER CABINET

Inner cabinet shall be all-aluminum construction. Cabinet shall be insulated with high density fiberglass. 1" on sides and top, and 1/4" on the back. Cabinet sides shall be constructed using 1/8" thick aluminum extrusion. Cabinet shall come standard with 7 sets of slides which shall be adjustable and removable. Cabinet shall accommodate 18" X 26", 14" X 18" trays and 12" X 20" hotel pans.



DOOR

Door exterior and interior will be 20 gauge aluminum and shall be insulated. Door shall have two heavy-duty, 5/8" thick extruded flag-type hinges. Door shall be removable without tools and shall have recessed handles. Door shall have a heavy-duty, positive action magnetic latch.



ELECTRICAL CHARACTERISTICS

Cabinet shall have a bottom mounted 1500 watt heating unit with front control panel consisting of: on-and-off switch, power indicator lights, and thermostat control. Heating unit shall be removable from the front. Cabinet shall be 120 volt, 60 cycles, 1 phase. Cabinet shall come with a cord and a Nema#5-15 plug.



CASTERS

Cabinet shall come complete with 4-2" non-marking plate casters, 2 rigid and 2 swivel. Casters shall have a weight capacity of 200 lbs each.



BASE

Base shall be .100 aluminum and shall be reinforced with 1/8" thick aluminum cross braces. Base shall come standard with non-marking perimeter bumper.



INTERNAL FRAME

Cabinet shall be framed with 1 1/2" X 1 1/2" X 1/8" thick 6063-T5 aluminum tubing in the front and back. Frame shall be fully welded.