

SECO

SELECT

TEST OUR METAL®



INSULATED MOBILE HEATER/PROOFER CABINET

For **18" X 26"**, **14" X 18"** Trays
and **12" X 20"** Hotel Pans

MODELS

**VCHI-35
RFM**

**VCHI-35
RFMG**

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacement for previously purchased equipment.

Job: _____

Item No. _____



MOBILE HEATER/PROOFER CABINET



Separate Heater and Proofer Controls.



Heavy-Duty Frame and Interlocking Side Panels of 6063-T5 architectural aluminum for air-tight seal and structural rigidity.



20 Gauge Aluminum Exterior for durability and cleanability.



Aluminum Interior for even heat retention and energy efficiency.



2250 Watts Heating Elements not exposed to water.



Double-Wall Construction with reinforcement channels welded between corner posts for added support and rigidity.



Heating Unit is removable from the front.



Doors open 270 degrees and are equipped with center-reinforcement and heavy-duty flag hinges. Comes standard with built-in flush mounted door handle and thermometer.



Heating Unit has a **Blower** and **Rear-Mounted Louvered Flue** to distribute heat evenly throughout cabinet.






Designed to hold **18" X 26"**, **14" X 18" Trays** and **12" X 20" Hotel Pans** with variable spacing on 3 1/8" centers. The tray slides are easily removable for cleaning.



Fully Insulated Top, Sides, Back, and Door for energy efficiency and heat retention.

MODEL SPECIFICATIONS



MODEL #	TRAY CAPACITY		PAN CAPACITY	HEIGHT	WIDTH	DEPTH	VOLTAGE	SHIPPING CUBE FEET	SHIP WEIGHT
	18" X 26"	14" X 18"	12" X 20"	DIM A	DIM B	DIM C			
VCHI-35-RFM	7	14	14	35 1/8"	26 1/2"	35 1/8"	120	25	150 Lbs.
VCHI-35-RFMG	7	14	14	35 1/8"	26 1/2"	35 1/8"	120	25	150 Lbs.



GENERAL

Cabinet shall be constructed with an aluminum exterior and interior. All double-wall construction insulated with high-density fiberglass insulation. All exterior surfaces shall be ground and polished to a #3 finish.



INNER CABINET

Inner cabinet shall be all aluminum construction. Cabinet shall be insulated with high-density fiberglass. 1" on sides and top, and 1/4" on the back. Cabinet sides shall be constructed using 1/8" thick aluminum extrusion. Cabinet shall come standard with 7 sets of slides which shall be adjustable and removable. Cabinet shall accommodate 18" X 26", 14" X 18" trays and 12" X 20" hotel pans. Cabinet shall be heated by the EvenHeat system. Cabinet shall come standard with a drip tray.



DOOR

Door exterior and interior will be 20 gauge aluminum and shall be insulated. Door shall have 2 heavy-duty, 5/8" thick, extruded flag-type hinges. Door shall be removable without tools and shall have recessed handles. Door shall have a heavy-duty, positive action magnetic latch.



ELECTRICAL CHARACTERISTICS

Cabinet shall have a bottom mounted, proofing/heating control panel consisting of: on/off switch, power indicator lights, and thermostat control. The 2250 watt EvenHeat system shall be removable from the front. Cabinet shall be 120 volt, 60 cycles, and 1 phase. Cabinet shall have a cord with a Nema #5-15 plug.



CASTERS

Cabinet shall come complete with 4-6" non-marking plate casters, 2 rigid and 2 swivel. Casters shall have a weight capacity of 250 lbs each.



BASE

Base shall be .100 aluminum and shall be reinforced with 1/8" thick aluminum cross braces.



INTERNAL FRAME

Cabinet shall be framed with 1 1/2" X 1 1/2" X 1/8" thick 6063-T5 aluminum tubing in the front and back. Frame shall be fully welded.



ACCESSORIES, OPTIONS, VARIATIONS



Top Perimeter Bumper



Transport Locks



Door Gaskets



Lexan Door



Left-Hand Door (no additional charge)



PTS - Pass Through



Perimeter Bumper Guard