

The SaniServ® model 407 Soft Serve Freezer is perfect for providing small servings, samplers, and adding a-la-mode to favorite desserts. The 407 is an economical addition to any restaurant with its affordable price and space saving countertop solution. The 407 is always a favorite among operators to supply a limited amount of soft serve ice cream and frozen yogurt products to keep customers coming back for more treats!

#### **DESIGNED FOR LOWER VOLUME APPLICATIONS**

Two - 4 oz. Servings per Minute - 7 Quart Capacity

#### Use SaniServ® Model 407 to Create













#### **Cooling Options**







**Dimensions:** Width (14") Depth (23.7") Height (25.4") Weight (145 lbs)

#### **Electrical Requirements:**

115/60/1 = 15 Amps208-230/60/1 = 10 Amps220-240/50/1 = 10 Amps (Extended Lead Times)



Up to 120 Cones / hr

We reserve the right to change specifications and product designs without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.







## MADE IN USA

## **SPACE SAVING** - Small Footprint Design

SaniServ® model 407 saves valuable floor space and turns the countertop into a real profit center by serving high profit ice cream and yogurt products.

## **EASY CLEANING AND OPERATION** - Fewer Parts = Simplified Cleaning

SaniServ® equipment is designed and built with the fewest parts to be disassembled, cleaned and sanitized than any other machine in the industry.

## **HIGH RETURN ON INVESTMENT** - Increased Profits

SaniServ® machines combine efficiency with consistent product quality and fast, quiet operation while insuring customer satisfaction with high profit ice cream or yogurt products.


## **QUALITY DESIGN** - Durability


SaniServ<sup>®</sup> machines are built to achieve long and dependable life through simplicity of design. Every machine is shipped standard with a stainless steel exterior, durable steel interior frame construction, heavy-duty components and consistency systems.


# MODEL 407

TORQUE CONSISTENCY CONTROLS

Minimum Wall Clearance Both Sides and Back 6 inches (152 mm)







| ELECTRICAL              |    |     |      | WIDTH       | HEIGHT      | DEPTH       | WEIGHT    | VOLUME          |
|-------------------------|----|-----|------|-------------|-------------|-------------|-----------|-----------------|
| VOLTS                   | Hz | Ph. | Amps | INCHES (MM) | INCHES (MM) | INCHES (MM) | LBS. (Kg) | CU FT. (cu. m.) |
| 115                     | 60 | 1   | 15   |             |             |             |           |                 |
| 208-230                 | 60 | 1   | 10   | 14 (356)    | 25.4 (645)  | 23.7 (602)  | 145 (66)  |                 |
| 220-240                 | 50 | 1   | 10   |             |             |             |           |                 |
| Shipping Specifications |    |     |      | 22.5 (571)  | 31.5 (800)  | 34.5 (876)  | 195 (89)  | 8.6 (.25)       |

### **SPECIFICATIONS**

#### **Cooling System:**

Air Only

## Dasher and Compressor Motors:

1/2 HP Dasher 1/2 HP Compressor

#### **Refrigerator Type:**

R404A

#### **Listings:**

UL, cUL, NSF

#### **FEATURES**

## **Evaporator and Mix Reservoir** Capacity:

7 Quarts (9.5 liters)

#### Dasher:

Heavy-Duty Stainless Steel with low friction scraper blades.

#### **Controls:**

Automatic consistency controls for improved consistency.

Tamper Proof Automatic Visual Mix Out System

#### **WARRANTY**

Parts 1 year Compressor 5 years Evaporator 5 years

#### **Options:**

Tune Up Kit Machine Stand Export Voltages